



| | |
|-----------------------------------|------------------------------|
| MODEL | F.RH-D |
| TYPE | FRAMELESS |
| CATEGORY | 2 SIDED |
| PIN CODE | B1650 |
| FUEL | GAS |
| POWER (KW) | |
| HEAT INPUT | |
| Nominal heat (hi) | 12.3 KW |
| Reduced heat (hi) | 4.9 KW |
| HEAT OUTPUT | |
| Nominal heat (hi) | 8.9 KW |
| Reduced heat (hi) | 3.6 KW |
| NATURAL GAS | YES |
| PROPANE GAS | YES |
| BUTANE GAS | YES |
| SMOKE GAS EXIT /AIR INTAKE | Ø 150-200MM |
| SYSTEM | |
| Fully remote controlled | GV60 MERTIK MAXITROL® |

REFERENCE GASES

| SUPPLY PRESSURE | INJECTOR SUPPLY PRESSURE | RATED INJECTOR PRESSURE | MAIN BURNER NOZZLE DIAMETER | PILOT BURNER DIAMETER | NOMINAL CONSUMPTION | REDUCED CONSUMPTION |
|------------------------|---------------------------------|--------------------------------|------------------------------------|------------------------------|----------------------------|----------------------------|
| 37 mbar | 37 mbar | 6.3 mbar | 1.5 mbar | 0.23 mm | 0.92 kg/h | 0.37 kg/h |