


|  |                                 |  |                     |
|--|---------------------------------|--|---------------------|
| <b>Flamme Rouge</b><br>Jbeil, Halat Main road, Bassam Bassil<br>Building, Lebanon<br><br>Brand name: ECO |                                 |  Certificate No : CE-9844 |                     |
| <b>Product Type:</b>   | Gas Fireplace                   |  |                     |
| <b>Product Name:</b>   | Frameless Gas<br>Fireplace      |  |                     |
| <b>Model Type:</b>   | FLAT Frameless Gas<br>Fireplace |  |                     |
| <b>Model Number:</b>   | F.FH-B130                       |  |                     |
| <b>Burner included</b>   | G.BUR 122                       | <b>Burner Specifications:</b>  |                     |
|  |                                 | <u>Power:</u>  |                     |
|  |                                 | Nominal heat (hi):   | 9.8 KW              |
|  |                                 | Reduced heat (hi):   | 3.9 KW              |
|  |                                 | <u>Heat output:</u>  |                     |
|  |                                 | Nominal heat (hi):   | 7 KW                |
|  |                                 | Reduced heat (hi):   | 2.8 KW              |
|  |                                 | <u>Electrical data:</u>  |                     |
|  |                                 | Voltage rating   | 6.0V                |
|  |                                 | <u>Fuel:</u>   |                     |
|  |                                 | Fuel:  | Propane Gas         |
|  |                                 | Gas system:  | Maxitrol syst. GV60 |
|  |                                 | Smoke Gas Exit /Air Intake:  | Ø 150-200mm         |
|  |                                 | Supply Pressure:   | 37 Mbar             |
|  |                                 | Injector Supply Pressure:  | 37 Mbar             |
|  |                                 | Rated Injector Pressure:   | 6.1Mbar             |
|  |                                 | Main Burner Nozzle Diameter:   | 1.5 Mbar            |
| Pilot Burner Diameter:   | 0.23 mm                         |  |                     |
| Nominal Consumption:   | 0.747 kg/h                      |  |                     |
| Reduced Consumption:   | 0.271 kg/h                      |  |                     |
| Burner Weight:   | 11.1 KG                         |  |                     |
| <b>Fireplace Material:</b>   | - Steel<br>-Vitro Ceramic Glass |  |                     |
| <b>Fireplace Weight:</b>   | 132 KG                          |  |                     |